

Pivot tables in Excel 2013

CONTENTS

1	Introduction	2
1.1	What are pivot tables?	2
1.2	Why use pivot tables?	2
2	Examples	2
3	Setting up data for pivot tables	3
4	Step-by-step instructions on how to create a first pivot table	4
4.1	Plan your table	4
4.2	Insert a pivot table	4
4.3	Initial setup	6
4.3.1	Calculate means (or averages)	7
4.4	Improve the look of the pivot table	9
4.4.1	Change the decimal places shown	9
4.4.2	Make nicer labels	9
4.4.3	Remove “Grand Totals”	10
5	Sample sizes	11
5.1	Count the number of entries before data is entered	11
5.2	Count the number of entered values	13
6	Means and standard deviations	14
6.1	Calculate means	14
6.2	Calculate standard deviations (sd)	15
7	Standard error of the mean (SEM) and coefficient of variation (%CV)	16
7.1	Coefficient of variation (%CV)	16
8	Blank rows	18
8.1	What happens if you include blank rows in the data rectangle?	18
8.2	What can you do about (blank) labels?	19
9	Create a pivot table from the values in another pivot table	20
9.1	Calculate average of sub-samples (or technical reps)	20
9.1.1	Create the first table	20
9.1.2	Hide subtotals and grand totals	22
9.1.3	Use tabular report layout	22
9.1.4	Fill in any “gaps” in the labels	23
9.2	Create a pivot table from another pivot table	24
10	Using filters with pivot tables	26
11	Sorting and changing the order of rows and columns	27
11.1	Use sort options to order row and column labels	27
11.1.1	Sort rows alphabetically in reverse	27
11.1.2	Sort rows by values	28
11.2	Manually sorting row and column labels	29
12	More complex table layouts	30
12.1	Tables with more than one summary	30

12.1.1	Several calculations for the same variable	30
12.1.2	Several variables in one table	31
12.1.3	A 3-way or 4-way table	32
13	Pivot charts?	34
14	Refreshing the pivot table.....	34
14.1	Manually refresh a pivot table	34
14.2	Automatically update a pivot table when file is opened	34
15	Adding to an existing table.....	35
15.1	Adding new rows of data	35
15.1.1	Add rows to the end of the data	35
15.1.2	Insert rows into the data source	36
15.1.3	Use an “over-size” data source range	37
15.2	Adding new columns of data	37
15.2.1	Adding new columns to the right of the data	37
15.2.2	Insert columns into the data source	38
16	Rearranging the raw data layout	39
16.1	Changing “wide” data to “long” (stacking data columns)	39
17	When Pivot tables aren’t enough	43

1 INTRODUCTION

This guide gives instructions on how to use pivot tables in Excel 2013, and has been written by PFR biometricians with feedback from researchers.

1.1 What are pivot tables?

Pivot tables are a flexible way of creating summary tables of results in Excel.

1.2 Why use pivot tables?

The main reason to use pivot tables for data summaries is that the summaries can be obtained without rearranging the data from the ideal format ([see these guidelines](#)).

Another reason to use pivot tables for data summaries instead of formulae is that no formulae are needed. Although summaries are easily calculated using formulae when just a single number is needed, when summary values are required for several groups (e.g., each level of a treatment factor, perhaps at different sites) then the formulae become numerous and more difficult to maintain, and users are more likely to rearrange data into inappropriate layouts so as to accommodate this. Pivot tables don't use formulae and are much easier to modify and maintain than multiple formulae.

2 EXAMPLES

The following are examples of datasets with pivot tables from research done at PFR.

Example 1

Disease incidence and severity and crop loss in grapes on several dates – the pivot table calculates means.

Date	Row	Bay	Incidence (%)	Severity (%)	% crop loss
14/03/2012	Row 2	Bay 5	6.7	1.00	0.07
14/03/2012	Row 2	Bay 15	0.0	0.00	0.00
14/03/2012	Row 2	Bay 25	0.0	0.00	0.00

Values			
Date	Average of Incidence (%)	Average of Severity (%)	Average of % crop loss
14/03/2012	1.37	0.43	0.02
21/03/2012	3.73	0.61	0.03
5/04/2012	14.90	2.19	0.36
14/04/2012	29.71	3.56	1.15

Example 2

Fungal growth under different concentrations of a fungicide – the pivot table calculates means for two experiments.

Exp	Product	concentration	dilut txt	rep	isolat	agar	plate	dot	incubator sl	Ass Date	days incub	growth (mm)
1	new	1	stock	1	Cp1	PDA	1	1	2	9-Jul-12	6	8
1	new	0.1	D1	1	Cp1	PDA	1	2	2	9-Jul-12	6	11
1	new	0.01	D2	1	Cp1	PDA	1	3	2	9-Jul-12	6	21
1	new	0.001	D3	1	Cp1	PDA	1	4	2	9-Jul-12	6	21

Mean growth (mm)	Experiment		
Concentration	1	2	Overall mean
0	32	34	33
0.000001	32		32
0.00001	32		32
0.0001	32	34	33
0.0005		33	33
0.001	14	32	21

3 SETTING UP DATA FOR PIVOT TABLES

To create a pivot table requires a dataset arranged in a single rectangle with data in a list down the columns with a row of unique column titles at the top.

Data is in lists going down columns

SampleID	Fruit	Temperature	Site	Result
1	Apples	5°C	Kerikeri	2
2	Apples	10°C	Kerikeri	8
3	Bananas	15°C	Kerikeri	9
4	Kiwifruit	5°C	Taupo	10

Every column has a title

- If a column title is missing (i.e, there is a blank cell instead), then Excel will give an error.



The PivotTable field name is not valid. To create a PivotTable report, you must use data that is organized as a list with labeled columns. If you are changing the name of a PivotTable field, you must type a new name for the field.

OK

- If a column title is duplicated, then Excel will add a number to the name wherever it appears in a pivot table. For example, if there were three different columns titled “Result”, the pivot table would use “Result”, “Result1”, and “Result2” to label the pivot table output.

4 STEP-BY-STEP INSTRUCTIONS ON HOW TO CREATE A FIRST PIVOT TABLE

4.1 Plan your table

- First think about how you want the table arranged, and what summary you want calculated.
- In this contrived example, we want a table with Site down the rows and Fruit across the columns. The summary values will be the mean of the “Result” variable. The table might look something like this:


Site	Fruit		
	Apples	Bananas	Kiwifruit
Kerikeri	-	-	-
Te Puke	-	-	-
Motueka	-	-	-
Clyde	-	-	-

4.2 Insert a pivot table


- Ensure that the data are suitably arranged for use in a pivot table (see Section 3 above). Select the data including the heading row.

SampleID	Fruit	Temperature	Site	Result
1	Apples	5°C	Kerikeri	2
2	Apples	10°C	Kerikeri	8
3	Bananas	15°C	Kerikeri	9
4	Kiwifruit	5°C	Te Puke	12
5	Apples	10°C	Te Puke	3
6	Kiwifruit	15°C	Te Puke	8
7	Bananas	5°C	Motueka	7
8	Kiwifruit	10°C	Motueka	15
9	Apples	15°C	Motueka	4


- Use the ribbon: Insert tab > Tables group > PivotTable.
A dialogue box will appear. By default the pivot table will be placed in a new worksheet (a new tab) in the file you are working on. This is most convenient when you are learning to use pivot tables as this means that there is no possible way the pivot table can collide with existing data. It also encourages the good practice of keeping your analysis separated from your data (something biometricians recommend you do).



- Click [OK] or press [Enter] to continue.
- A new sheet will be created. Depending on the names of the existing sheets, the new sheet will be named either Sheet1 or Sheet2, etc. At the left of the new sheet is a blank pivot table with some brief instructions.



- At the right of the sheet is the pivot table Fields List. This is used to create the layout of the table.



4.3 Initial setup

- Drag-and-drop the appropriate titles (called “fields”) into the appropriate Columns, Rows, and Values boxes. In this case, drag-and-drop Fruit into the Columns area, Site into the Rows area, and Result into the values area. As each field is added, the pivot table updates to reflect the change. The PivotTable Field dialogue and the resulting pivot table are shown below with coloured circles highlighting the chosen fields.

PivotTable Fields

Choose fields to add to report: ⚙️

- ☐ SampleID
- ☒ **Fruit**
- ☐ Temperature
- ☒ **Site**
- ☒ **Result**

MORE TABLES...

Drag fields between areas below:

⏚ FILTERS

|||| COLUMNS

Fruit

≡ ROWS

Site

Σ VALUES


Sum of Result

☐ Defer Layout Update UPDATE



Sum of Result	Column Labels			
Row Labels	Apples	Bananas	Kiwifruit	Grand Total
Clyde	83	56	92	231
Kerikeri	142	46	180	368
Motueka	84	77	156	317
Te Puke	72	161	56	289
Grand Total	381	340	484	1205

4.3.1 Calculate means (or averages)

- Note that by default, Excel has calculated the **sum** of the values. To change the calculation to the average, right-click on any of the *values* in the pivot table then select: **S**ummarize Values By > **A**verage.



- Alternatively, use the “Value Field Settings...” dialogue by either right-click on a pivot table value > Value Field Settings..., or click on the Result dropdown (showing as “Sum of Results”) in the values box and choose Value Field Settings...
In the Value Field Settings dialogue box, select Summarize value field by: Average.




- The pivot table will now show the averages. Note that the “Grand Total” row at the bottom and column at the right are now the averages.

Average of Result				
Column Labels	Apples	Bananas	Kiwifruit	Grand Total
Row Labels				
Clyde	13.83333333	14	13.14285714	13.58823529
Kerikeri	15.77777778	11.5	16.36363636	15.33333333
Motueka	16.8	8.555555556	19.5	14.40909091
Te Puke	10.28571429	23	11.2	15.21052632
Grand Total	14.11111111	14.16666667	15.61290323	14.69512195

4.4 Improve the look of the pivot table

4.4.1 Change the decimal places shown

- We can improve the appearance of the pivot table by showing the means to only one decimal place. Right-click on any number in the pivot table > Number Format..., then in the Format Cells dialogue box that appears, select Number, and set Decimal places to 1.



Average of Result Column Labels ▼				
Row Labels ▼	Apples	Bananas	Kiwifruit	Grand Total
Clyde	13.8	14.0	13.1	13.6
Kerikeri	15.8	11.5	16.4	15.3
Motueka	16.8	8.6	19.5	14.4
Te Puke	10.3	23.0	11.2	15.2
Grand Total	14.1	14.2	15.6	14.7


4.4.2 Make nicer labels

- We can also edit the labels used on the pivot table. The pivot table has produced default labels of "Average of Result", "Column Labels", "Row Labels" and "Grand Total". To edit any of these labels, simply select the cell (either by using arrow keys or by clicking on the cell) and type in the new label.

Mean result	Fruit			
Site	Apples	Bananas	Kiwifruit	Overall mean
Clyde	13.8	14.0	13.1	13.6
Kerikeri	15.8	11.5	16.4	15.3
Motueka	16.8	8.6	19.5	14.4
Te Puke	10.3	23.0	11.2	15.2
Overall mean	14.1	14.2	15.6	14.7

4.4.3 Remove “Grand Totals”

- By default, a pivot table contains grand totals (here relabelled as “Overall mean”). These can easily be removed if needed. Ensure the pivot table tools are visible in the ribbon by clicking anywhere on the pivot table. On the ribbon: Design tab > Layout group > Grand Totals dropdown, select the option that suits. In this example, the “totals” will be removed from both rows and columns.



- The finished pivot table of means.

	A	B	C	D
1				
2				
3	Sum of Result Fruit			
4	Site	Apples	Bananas	Kiwifruit
5	Clyde	83.0	56.0	92.0
6	Kerikeri	142.0	46.0	180.0
7	Motueka	84.0	77.0	156.0
8	Te Puke	72.0	161.0	56.0

5 SAMPLE SIZES

A simple use of pivot tables is to count the number of entries in a dataset. This can be done by counting either the entered result values or by counting the rows of one of the factor columns.

5.1 Count the number of entries before data is entered

Typically, an experiment or trial is planned and the data spreadsheet can be setup before any data is collected. This may well have been done for you by a biometrician when they created the randomisation for the sampling or treatment allocations.

- In this example, we want to know how replicates there are of each of the “Fruit” and “Temperature” treatments.

SampleID	Fruit	Temperature	Rep	Result1	Result2
1	Apples	15	1		
2	Kiwifruit	5	1		
3	Bananas	10	1		
4	Apples	10	1		

No data
entered yet

- First, create the pivot table in the usual way (see Section 4 above). For the “VALUES” field, use one of the row or column factors. In this example, we can use either “Fruit” or “Temperature”. Because the “Fruit” contains text labels, Excel will default to providing a Count of Fruit. In contrast, because “Temperature” contains only numbers, Excel defaults to providing a Sum of Temperature.

Choose fields to add to report:

- ☐ SampleID
- ☒ Fruit
- ☒ Temperature
- ☐ Rep
- ☐ Result1
- ☐ Result2

MORE TABLES...

Drag fields between areas below:

FILTERS

ROWS
Fruit

COLUMNS
Temperature

VALUES
Sum of Temperature


☐ Defer Layout Update

UPDATE


“Temperature” is both a
Column field and a
Value field.

Change “Sum” to “Count”

- To change the calculation from sum to the count, right-click on any of the *values* in the pivot table then select: **Summarize Values By > Count**.



- Alternatively, use the “Value Field Settings...” dialogue by either right-click on a pivot table value > Value Field Settings..., or click on the Result dropdown (showing as “Sum of Temperature”) in the values box and choose Value Field Settings... In the Value Field Settings dialogue box, select Summarize value field by: **Count**.



- The pivot table should now show counts of the combinations of rows and column factors. These count equal the number of rows available for data in the dataset.


Count of Temperature		Temperature			
Fruit		5	10	15	Grand Total
Apples		4	4	4	12
Bananas		4	4	4	12
Kiwifruit		4	4	4	12
Grand Total		12	12	12	36

5.2 Count the number of entered values

After data has been entered into a dataset, the number of entered values can easily be obtained using a pivot table.

- First, create the pivot table in the usual way (see Section 4 above). Ensure that you use the data column that is the variable of interest as the “VALUES”. In this example, we want to know how many values there are for “Result2” (which has some empty cells).


SampleID	Fruit	Temperature	Rep	Result1	Result2
1	Apples	15	1	9.6	
2	Kiwifruit	5	1	9.7	4
3	Bananas	10	1	7.0	2
4	Apples	10	1	7.6	
5	Bananas	15	1	10.8	2
6	Kiwifruit	15	1	11.3	3
7	Kiwifruit	10	1	8.3	2
8	Bananas	10	1	7.0	


Choose fields to add to report: 


- ☐ SampleID
- ☒ Fruit
- ☒ Temperature
- ☐ Rep
- ☐ Result1
- ☒ Result2


MORE TABLES...

Drag fields between areas below:

 FILTERS

 COLUMNS

 ROWS

 VALUES

Fruit

Temperature

Count of Result2

☐ Defer Layout Update UPDATE

- The pivot table values may be counts already, but if not (they would likely show as a “Sum of ...”, then change the calculation type to “Count” (see Section 5.1 above).
- In this case, there are several counts that are not as expected (all values should be 4 with a grand total of 36, see the pivot table in Section 5.1 above). Two of the Apple temperature treatments have 3 values instead of 4, and the Bananas, temperature 5 combination has no entered data at all. NB: any zero counts are shown as blank rather than “0”.

Count of Result2 Temperature ▾				
Fruit ▾	5	10	15	Grand Total
Apples	4	3	3	10
Bananas		4	4	8
Kiwifruit	4	4	4	12
Grand Total	8	11	11	30

Zero counts are shown as blank


6 MEANS AND STANDARD DEVIATIONS

The default summary created by a pivot table is either the sum of the values or the count of the number of values. It is easy to change this summary to the mean or standard deviation.


6.1 Calculate means

To calculate means, first create the pivot table in the usual way (see Section 4 above).

- Then, either right-click on any value in the pivot table > Summarize Values By > Average




- Or, right-click on any value in the pivot table > Value Field Settings...
- In the dialogue that appears, select "Average", then press [Enter] or click [OK].




6.2 Calculate standard deviations (sd)

To calculate standard deviations, first create the pivot table in the usual way (see Section 4 above).

- Then, either right-click on any value in the pivot table > Summarize Values By > More Options...



- Or, right-click on any value in the pivot table > Value Field Settings...
- In the dialogue that appears, select "StdDev", then press [Enter] or click [OK].



Note: Do NOT use “StdDevp” (which is population standard deviation). You are unlikely to ever need this value; if you think that you do, you are recommended to check this with a biometrician.

7 STANDARD ERROR OF THE MEAN (SEM) AND COEFFICIENT OF VARIATION (%CV)

You cannot get either the standard error of the mean (SEM) or the coefficient of variation (%CV) to appear directly in a pivot table in Excel 2013. However, you can use pivot tables to help with the calculation. The $SEM = s/\sqrt{n}$ and $\%CV = s/\bar{x} \times 100\%$ where s = standard deviation, n = sample size, and \bar{x} = sample mean. You can create two pivot tables, one to display the standard deviation, and for the SEM, the other to display the sample size, or for %CV the mean, and then use formulae to calculate the SEM or %CV values somewhere adjacent to the pivot tables.

7.1 Coefficient of variation (%CV)


To create a table of %CV values (coefficient of variation) two pivot tables are needed, one showing standard deviations, the other showing means.

In this example, a pivot table of standard deviations will be created on a new sheet, then a pivot table of means will be created beside it

- First, create a pivot table showing the standard deviations (see Sections 4 and 6.2 above).

	A	B	C	D	E	F
1						
2						
3	Row Labels	StdDev of Result				
4	Apples	8.841916488				
5	Bananas	10.76898391				
6	Kiwifruit	9.0615577				
7	Grand Total	9.43161092				


- Then, add a pivot table showing the means. In this example, we will place the means table beside the s.d. table (rather than on a separate sheet). Select the same data and use the ribbon: Insert tab > Tables group > PivotTable.
- In the “Create PivotTable” dialogue, change “New Worksheet” to “Existing Worksheet” and pick a location beside the s.d. pivot table.



- Make a pivot table of means (see Section 6.1 above) with the **same layout** as the table of standard deviations.

Row Labels	StdDev of Result	Row Labels	Average of Result
Apples	8.841916488	Apples	14.11111111
Bananas	10.76898391	Bananas	14.16666667
Kiwifruit	9.0615577	Kiwifruit	15.61290323
Grand Total	9.43161092	Grand Total	14.69512195

- Before making the formula for the calculation of %CV, ensure that the pivot table setting “Generate GetPivotData” is unchecked. To do this, click anywhere on any pivot table, then use the ribbon: Analyze tab > PivotTable group (which is on the very left of the ribbon) > Options dropdown. If “Generate GetPivotData” shows a tick, select this item to turn the tick off.



This setting applies to all pivot tables and, although not essential, it makes easier the creation of formulae that use pivot table results.

- Create the coefficient of variation formulae. In some convenient location, probably either to the right of or below the pivot tables, enter the formula to calculate $s/\bar{x} \times 100\%$.

Row Labels	StdDev of Result	Row Labels	Average of Result	
Apples	8.841916488	Apples	14.11111111	=B4/E4*100
Bananas	10.76898391	Bananas	14.16666667	
Kiwifruit	9.0615577	Kiwifruit	15.61290323	

- Copy the formula to all of the appropriate cells (in this example, down the next two rows).
- You can also copy labels across (using formulae is best) and reduce the number of decimal places displayed.

Row Labels	StdDev of Result	Row Labels	Average of Result	Row Labels	%CV
Apples	8.841916488	Apples	14.11111111	Apples	62.7
Bananas	10.76898391	Bananas	14.16666667	Bananas	76.0
Kiwifruit	9.0615577	Kiwifruit	15.61290323	Kiwifruit	58.0

- Note, an alternative to creating two tables is to have the standard deviation and the mean both appear in the same table. This can work well for 1-way tables, but not for 2-way tables or those with more complex layouts.

Row Labels	StdDev of Result	Average of Result2	Row Labels	%CV
Apples	8.841916488	14.11111111	Apples	62.7
Bananas	10.76898391	14.16666667	Bananas	76.0
Kiwifruit	9.0615577	15.61290323	Kiwifruit	58.0

8 BLANK ROWS

Blank rows are unnecessary in a dataset – they add nothing to the data, but are sometimes added by users wanting to have visual breaks in the list of data. They can, however, be temporarily included at the bottom of a dataset in preparation for further data entry.

8.1 What happens if you include blank rows in the data rectangle?

When blank rows are included in a dataset, then pivot tables will include an extra “(blank)” category for each row and column field.

Here is an example dataset that includes blank rows:

SampleID	Fruit	Temperature	Site	Result
1	Apples	5°C	Kerikeri	2
2	Apples	10°C	Kerikeri	8
3	Bananas	15°C	Kerikeri	9
		A blank row...		
4	Kiwifruit	5°C	Te Puke	12
5	Apples	10°C	Te Puke	3
6	Kiwifruit	15°C	Te Puke	8
		A 2 nd blank row...		
7	Bananas	5°C	Motueka	7

The resulting pivot table has a (blank) category added to both the rows and columns:


Count of Result	Fruit				
Site	Apples	Bananas	Kiwifruit	(blank)	Grand Total
Clyde	6	4	7		17
Kerikeri	9	4	11		24
Motueka	5	9	8		22
Te Puke	7	7	5		19
(blank)				(blank)	
Grand Total	27	24	31		82

8.2 What can you do about (blank) labels?

If you are happy to have the “(blank)” label used in the table, you need do nothing. However, if you want to eliminate the “(blank)” labels, simply edit the dataset and delete the blank rows from within it. If the blank rows are at the bottom of the dataset in preparation for further data entry, then you can either change the pivot table data source to exclude these rows, or enter the values you know into the fields used for the pivot table rows and columns (these are usually treatment or replicate info).

Alternatively, if you must have the blank rows in the dataset yet want to remove the labels from the pivot table, then you can selectively exclude the “(blank)” labels.

- On the pivot table, click on the dropdown for the field containing the “(blank)” labels. In this example, the “Fruit” dropdown was clicked. In the dialogue box that appears, deselect “(blank)” and press [Enter] or click [OK].



- The pivot table is updated to exclude the “(blank)” labels from the Fruit field. Because the “(blank)” fruit are also the blank sites, using a filter on Fruit also removes the “(blank)” label from the Site rows.

Count of Result	Fruit			
Site	Apples	Bananas	Kiwifruit	Grand Total
Clyde	6	4	7	17
Kerikeri	9	4	11	24
Motueka	5	9	8	22
Te Puke	7	7	5	19
Grand Total	27	24	31	82

9 CREATE A PIVOT TABLE FROM THE VALUES IN ANOTHER PIVOT TABLE

Sometimes you need to create a pivot table from data in another pivot table. A typical example of this is when each replicate of a treatment (sometimes known as a “biological rep”) has data collected from each of several sub-samples (sometimes known as a “technical reps” or “lab replicates”). To get the treatment means, first you would average the sub-samples (for each treatment and biological rep), then for each treatment you would calculate the mean of the sub-sample means. The two stages of calculation can be done using two pivot tables.

9.1 Calculate average of sub-samples (or technical reps)

Collection of data from sub-samples or taking a measurement (or performing an assay) several times from the same sample is typically done when the measurement (or assay) result is known to vary, or the measurement process has some uncertainty, and so the researcher takes several measures and then averages those to get a single more reliable result for each sample. It is the averages (rather than the sub-sample results) that are then used for further analysis.

Note, if you want find out more about why you should average the results of such sub-samples or “technical” reps, please talk with any of the [PFR biometricians](#).

Some examples of research that would generates results from “sub-samples” are:

Example 1: Separate apple trees had different fungicide treatments applied to them. From each tree, 20 fruit were assessed for the effects of disease. Each apple is a sub-sample of the tree that received the treatment.

Example 2: Soil samples taken from different regions were assessed for their hydrophobicity using a test which measures the time taken for a drop of water to go into soil. Each soil sample was assessed three times.

9.1.1 Create the first table

In the following example, each individual sample (denoted by SampleID) has been assessed in triplicate (as indicated by the Triplicate column in the screenshot below).

To calculate the averages:

- First create the pivot table in the usual way (see Section 4 above).
- Make the calculation be averages (see Section 6.1 above).

SampleID	Fruit	Temperature	Rep	Triplicate	Result
1	Kiwifruit	15	1	1	17
1	Kiwifruit	15	1	2	16
1	Kiwifruit	15	1	3	17
2	Bananas	10	1	1	6
2	Bananas	10	1	2	5
2	Bananas	10	1	3	6
3	Apples	10	1	1	5
3	Apples	10	1	2	6
3	Apples	10	1	3	6
4	Kiwifruit	10	1	1	16
4	Kiwifruit	10	1	2	14
4	Kiwifruit	10	1	3	13

The layout of the pivot table is created by using all of the data columns that uniquely identify the samples as the Row fields. This will include any treatment factors as well as any blocking factors (such as Block, Rep, Tree, Orchard Row, Batch, Run, etc.) that describe the statistical design of the experiment.

PivotTable Fields

Choose fields to add to report:

- ☒ SampleID
- ☒ Fruit
- ☒ Temperature
- ☒ Rep
- ☐ Triplicate
- ☒ Result

MORE TABLES...

Drag fields between areas below:

FILTERS

COLUMNS

ROWS

SampleID
Fruit
Temperature
Rep

VALUES

Average of Result

☐ Defer Layout Update

UPDATE

Row Labels | **Average of Result**

1	16.66666667
Kiwifruit	16.66666667
15	16.66666667
1	16.66666667
2	5.66666667
Bananas	5.66666667
10	5.66666667
1	5.66666667
3	5.66666667
Apples	5.66666667
10	5.66666667
1	5.66666667
4	14.33333333

9.1.2 Hide subtotals and grand totals

The subtotals and grand totals need to be removed:


- To remove or hide the subtotals, first click anywhere on the pivot table to ensure that the pivot table tools are visible in the ribbon. Then, on the ribbon: Design tab > Layout group > Subtotals dropdown > Do Not Show Subtotals.
- Similarly, to remove or hide the “grand totals” (also see Section 4.4.3) use the ribbon: Design tab > Layout group > Grand Totals dropdown > Off for Rows and Columns.

Row Labels	Average of Result
1	
Kiwifruit	
15	
1	16.66666667
2	
Bananas	
10	
1	5.666666667
3	

9.1.3 Use tabular report layout

Excel has three different forms of report layout. The default is the Compact form which puts all of the row labels into a single column. The Outline form puts the row label fields (if there are more than one) into separate columns but on different rows, and the Tabular form additionally puts the row labels into the same row. It is the tabular form that we need because this creates a rectangular data layout suitable for use in further data analysis.

- To use the tabular form, first click anywhere on the pivot table to ensure that the pivot table tools are visible in the ribbon. Then, on the ribbon: Design tab > Layout group > Report Layout dropdown > Show in Tabular Form.



The resulting pivot table has the row fields (SampleID, Fruit, Temperature, Rep) in separate columns, and the labels for each average in the same row.

SampleID	Fruit	Temperature	Rep	Average of Result
1	Kiwifruit	15	1	16.66666667
2	Bananas	10	1	5.666666667
3	Apples	10	1	5.666666667
4	Kiwifruit	10	1	14.33333333

Note that a count of the Result variable shows (in a separate pivot table below) that the sample size for each row in the pivot table is 3 (because there are 3 triplicates summarised in each row value).

SampleID	Fruit	Temperature	Rep	Count of Result
1	Kiwifruit	15	1	3
2	Bananas	10	1	3
3	Apples	10	1	3
4	Kiwifruit	10	1	3

9.1.4 Fill in any “gaps” in the labels

In the example above there is a single field (a column in the data) that contains a unique sample identifier (i.e., SampleID) that uniquely identifies each sample. If, for example, SampleID was not present and the samples were instead uniquely identified by the combination of two or more other columns (in this case, Fruit, Temperature and Rep), then the tabular layout will produce a pivot table with “gaps” in the labels.

Fruit	Temperature	Rep	Average of Result
Apples	5	1	2.666666667
		2	3
		3	4
		4	7
	10	1	5.666666667
		2	5
		3	10
		4	10
	15	1	10.66666667
		2	10.66666667
		3	13.33333333
		4	14.33333333

Gaps in the Fruit and Temperature labels

To fill the gaps in the labels:

- Use the ribbon: Design tab > Layout group > Report Layout dropdown > Repeat All Item Labels

Fruit	Temperature	Rep	Average of Result
Apples	5	1	2.666666667
Apples	5	2	3
Apples	5	3	4
Apples	5	4	7
Apples	10	1	5.666666667
Apples	10	2	5
Apples	10	3	10
Apples	10	4	10
Apples	15	1	10.66666667
Apples	15	2	10.66666667
Apples	15	3	13.33333333
Apples	15	4	14.33333333

9.2 Create a pivot table from another pivot table

NB: Before creating a pivot table from the values in another pivot table, **ensure that the first pivot table** is set up suitably and **has no subtotals or grand totals showing** (see Section 9.1.2), **and uses a tabular layout** (see Section 9.1.3) **without any gaps in the row labels** (see Section 9.1.4).

To create a second pivot table from the first one:

- First make sure that you have selected a cell that is **not** part of a pivot table (otherwise the Insert PivotTable option will be greyed out).
- Use the ribbon: Insert tab > Tables group > PivotTable.
- In the Create PivotTable dialogue, you need to select the data range to be **all of the values and heading row of the first pivot table**. You are recommended to place the second pivot table on a new worksheet. Click [OK] to close the dialogue.

SampleID	Fruit	Tem	Rep	Average of Result
1	Kiwifruit	15	1	16.66666667
2	Bananas	10	1	5.666666667
3	Apples	10	1	5.666666667
4	Kiwifruit	10	1	14.33333333
5	Bananas			

Create PivotTable

Choose the data that you want to analyze

☒ **Select a table or range**

Table/Range:

☐ **Use an external data source**

Connection name:

Choose where you want the PivotTable report to be placed

☒ **New Worksheet**

☐ **Existing Worksheet**

Location:

Choose whether you want to analyze multiple tables

☐ **Add this data to the Data Model**

Then create the pivot table by arranging the fields into the desired columns and rows, and by selecting the appropriate calculation for the results (see Section 4.3 above). In this example, the mean result will be calculated for the combinations of Fruit and Temperature:

Choose fields to add to report:

☐ SampleID

☒ **Fruit**

☒ **Temperature**

☐ Rep

☒ **Average of Result**

MORE TABLES...

Drag fields between areas below:

FILTERS

COLUMNS

ROWS

VALUES

☐ Defer Layout Update

Mean result	Fruit		
Temperature	Apples	Bananas	Kiwifruit
5	4.2	2.9	11.5
10	7.7	7.2	15.3
15	12.3	11.3	18.5

10 USING FILTERS WITH PIVOT TABLES

In addition to choosing which fields to use for the row or column labels, you can also choose one or more fields to be overall filters for the pivot table. In the example below, the Fruit field has been added as a filter, and the results filtered to show only those results from Apples.

- To enable filtering, click anywhere in the pivot table to make the PivotTable Fields dialogue appear, then drag-and-drop the desired filter field (in this case, "Fruit") into the "FILTERS" area.

Pivot table without a filter

Site	Mean Result
Kerikeri	15.3
Te Puke	15.2
Motueka	14.4
Clyde	13.6
Overall mean	14.7

Drag fields between areas below:

FILTERS	COLUMNS
Fruit	
ROWS	VALUES
Site	Mean Result

Filter enabled for "Fruit"

Fruit	Site	Mean Result
(All)	Kerikeri	15.3
(All)	Te Puke	15.2
(All)	Motueka	14.4
(All)	Clyde	13.6
(All)	Overall mean	14.7

- To apply a filter, click on the filter field's dropdown, and select from the list shown. Here "Apples" is selected.

2 Fruit (All)

Search

- (All)
- Apples
- Bananas
- Kiwifruit

☐ Select Multiple Items

OK Cancel

- Press [Enter] or click [OK] and the filter will be applied. The pivot table now shows a subset of the available results – only the means for Apples are shown

Fruit	Apples
Site	Mean Result
Kerikeri	15.8
Te Puke	10.3
Motueka	16.8
Clyde	13.8
Overall mean	14.1

Filter is applied, limiting the results to those for "Apples"

11 SORTING AND CHANGING THE ORDER OF ROWS AND COLUMNS

By default, Excel sorts column and row labels into alphabetical (or numerical) order. The order of rows (or columns) can be changed by either sorting using built-in sort options or manual rearrangement.


11.1 Use sort options to order row and column labels

11.1.1 Sort rows alphabetically in reverse

The default appearance of text labels is to sort them alphabetically from A to Z. It is easy to reverse this sorting so that the labels are sorted from Z to A instead.

To sort row labels alphabetically in reverse order:

- Create the pivot table of means.
- Either click on the dropdown for the field, then select "Sort Z to A".



- Or, right-click on any of the labels > select Sort > "Sort Z to A".

Site	Mean Result
Clyde	13.6
Kerikeri	15.3
Motueka	14.4
Te Puke	15.2
Overall mean	14.7

Site	Mean Result
Clyde	13.6
Kerikeri	15.3
Motueka	14.4
Te Puke	15.2
Overall mean	14.7

Site	Mean Result
Kerikeri	15.3
Motueka	14.4
Te Puke	15.2
Clyde	13.6
Overall mean	14.7

- Similarly, move “Te Puke” above “Motueka”. Hover the mouse over the edge of the Te Puke label cell until the “move” pointer appears, then click and drag the mouse up until the indicator is above Motueka. Release the mouse button and Te Puke will have been moved.

Site	Mean Result
Kerikeri	15.3
Motueka	14.4
Te Puke	15.2
Clyde	13.6
Overall mean	14.7

Site	Mean Result
Kerikeri	15.3
Motueka	14.4
Te Puke	15.2
Clyde	13.6
Overall mean	14.7

Site	Mean Result
Kerikeri	15.3
Te Puke	15.2
Motueka	14.4
Clyde	13.6
Overall mean	14.7

Manual sorting can be applied equally well to columns as to rows.

12 MORE COMPLEX TABLE LAYOUTS

12.1 Tables with more than one summary

12.1.1 Several calculations for the same variable

A variable can be added to a pivot table not just once but multiple times so that several calculations can be made on that variable within a single pivot table. For example, you can show the mean, standard deviation, and sample size for a variable all in the same pivot table.


In the following example, for each fruit type the mean, s.d. and sample size are calculated for the “Result” variable:

- To begin, create the pivot table showing the average of the variable (see Section 4 above). Note that in the pivot table shown below some of the titles have been edited and the means formatted to display only one decimal place.

FILTERS		COLUMNS	
ROWS	VALUES		
Fruit	Average of Result		


Fruit	Average of Result
Apples	14.1
Bananas	14.2
Kiwifruit	15.6
Grand Total	14.7

- To add the standard deviations, in the PivotTable Field dialogue, drag the “Result” variable again into the “Values” box. Then change the calculation to “StdDev” (see Section 6.2).
- To add the sample sizes, in the PivotTable Field dialogue, drag the “Result” variable into the “Values” box a third time. Then change the calculation to “Count” (see Section 5.2).



Fruit	Average of Result	StdDev of Result	Count of Result
Apples	14.1	8.84	27
Bananas	14.2	10.77	24
Kiwifruit	15.6	9.06	31
Overall	14.7	9.43	82

- Note that after dragging the “Result” variable into the “Values” box several times, if the calculation is the same for two or more instances of the variable, then Excel will **rename** the variable in the pivot table. For example, the second and third instance of “result” will be renamed “Result2” and “Result3”. Excel does this because it does not allow two calculated results to have the same title.




- To correct the titles, **first** change to calculation to the one desired (see Sections 6.1, 6.2 and 5.2), **then** edit the titles (see Section 4.4.2).

12.1.2 Several variables in one table

A pivot table need not be limited to the results from a single variable but can include results from more than one variable. For example, for a dataset containing results for “Length”, “Weight” and “pH”, you could show the means for all three variables all in the same pivot table.

- To begin, create the pivot table by dragging-and-dropping “Site” into the Rows box, and “Length” into the Values box of the PivotTables Fields dialogue (see Section 4.3). Then, drag-and-drop the “Weight” and “pH” variables into the Values box.



Row Labels	Sum of Length	Sum of Weight	Sum of pH
Clyde	231	2051.761847	118.1
Kerikeri	368	3239.542529	170
Motueka	317	2829.211868	155
Te Puke	289	2585.608127	129.5
Grand Total	1205	10706.12437	572.6

- Then change the calculation for each field from the default **Sum** to the desired **Average** (see Sections 4.3.1 or 6.1 above). Note that in the pivot table shown below some of the titles have been edited, and the means formatted to display only one decimal place.

Site	Average of Length	Average of Weight	Average of pH
Clyde	13.6	120.7	6.9
Kerikeri	15.3	135.0	7.1
Motueka	14.4	128.6	7.0
Te Puke	15.2	136.1	6.8
Overall	14.7	130.6	7.0

12.1.3 A 3-way or 4-way table

A pivot table need not have just one row or column field, but can have several (the actual number is limited only by the computer memory available).

- To create a 3-way pivot table, either create a new table (see Section 4 above) or edit an existing table.

The screenshot shows the 'Choose fields to add to report:' section with the following fields selected: ☒ Fruit, ☒ Temperature, ☒ Site, and ☒ Result. Below this, the 'Drag fields between areas below:' section shows the following layout:

- FILTERS:** (Empty)
- COLUMNS:** Site, Temperature
- ROWS:** Fruit
- VALUES:** Count of Result

At the bottom, there is a checkbox for 'Defer Layout Update' and an 'UPDATE' button.


Two fields used for columns:
"Site", then "Temperature"

The resulting pivot table (which has been edited to remove subtotals and grand totals) has two sets of Column labels, the first row is Site, and the second row is Temperature.

Count of Result	Column Labels											
Row Labels	Clyde			Kerikeri			Motueka			Te Puke		
	5°C	10°C	15°C	5°C	10°C	15°C	5°C	10°C	15°C	5°C	10°C	15°C
Apples	2	2	2	2	4	3	1	3	1	3	1	3
Bananas	1	1	2	2	1	1	1	5	3	2	4	1
Kiwifruit	1	2	4	4	4	3	2	3	3	1	3	1

- To rearrange the pivot table, click on anywhere in the pivot table to make the PivotTable Fields dialogue appear, then drag-and-drop the fields into the new arrangement. In the example below, the Temperature field has been dragged from the Columns box to the Rows box so that the table rows are now representing both the Fruit and Temperature.

Two fields used for rows:
"Fruit" and "Temperature"

Choose fields to add to report: 

☐ SampleID
☒ Fruit
☒ Temperature
☒ Site
☒ Result

MORE TABLES...

Drag fields between areas below:

FILTERS **COLUMNS**

ROWS **VALUES**

Site

Fruit

Temperature

Count of Result

☐ Defer Layout Update UPDATE

Count of Result	Column Labels			
Row Labels	Clyde	Kerikeri	Motueka	Te Puke
Apples				
5°C	2	2	1	3
10°C	2	4	3	1
15°C	2	3	1	3
Bananas				
5°C	1	2	1	2
10°C	1	1	5	4
15°C	2	1	3	1
Kiwifruit				
5°C	1	4	2	1
10°C	2	4	3	3
15°C	4	3	3	1

13 PIVOT CHARTS?

Pivot charts do not seem to be a lot of use – a trellis plot by a statistics package is usually much better. One limitation of pivot charts is that you cannot create x-y scatter plots – Excel always uses a category-type axis which puts that categories at equal spacing from each other regardless of any numerical values involved. For example, if samples were taken at 1, 2, 4 and 8 hours, then the pivot

chart would space these times equally:  rather than .

14 REFRESHING THE PIVOT TABLE


WARNING: unlike calculated formulae, pivot tables do **NOT** automatically update when the source data has been changed. They need to be refreshed in order to be recalculated.

14.1 Manually refresh a pivot table


If you change any of the data, the pivot table needs to be refreshed before the new data can appear in the table.

To refresh a pivot table:

- Either, click anywhere in the pivot table and use the keyboard shortcut [Alt+F5].
- Or, right-click anywhere in the pivot table and select “Refresh” from the menu.




- Or, click anywhere in the pivot table and use the ribbon: Analyze tab > Data group > Refresh dropdown > Refresh.




14.2 Automatically update a pivot table when file is opened

To have a pivot table automatically refresh whenever the spreadsheet file is opened:

- Click anywhere in the pivot table and use the ribbon: Analyze tab > PivotTable group > Options dropdown > Options.



- In the PivotTable Options dialogue that appears, select the “data” tab and tick “Refresh data when opening the file”. Click [OK] or press [Enter].



15 ADDING TO AN EXISTING TABLE


15.1 Adding new rows of data

After creating a pivot table, if you add more data to the source for the pivot table then you need to ensure that this data is added to the pivot table calculations. There are several ways that this can be done.

15.1.1 Add rows to the end of the data

After adding extra rows of data to the bottom of a pivot table data source, the data source needs to be updated. To update the data source:

- Click anywhere on the pivot table to ensure that the pivot table tools are visible in the ribbon.
- On the ribbon: Analyze tab > Data group > Change Data Source
- The “Change PivotTable Data Source” dialogue will appear.



- The cells used for the data source are shown:

3	SampleID	Fruit	Temperature	Site	Result
22	19	Apples	5°C	Motueka	24
23	20	Kiwifruit	5°C	Motueka	27
24	21	Kiwifruit	5°C	Motueka	17
25	22	Kiwifruit	5°C	Clyde	1
26	23	Apples	5°C	Clyde	4
27					

New data rows
to be added

- Extend the selection to include the extra rows (**Tip:** hold down the Shift key and press [Down arrow] to extend the selection downwards):

3	SampleID	Fruit	Temperature	Site	Result
22	19	Apples	5°C	Motueka	24
23	20	Kiwifruit	5°C	Motueka	27
24	21	Kiwifruit	5°C	Motueka	17
25	22	Kiwifruit	5°C	Clyde	1
26	23	Apples	5°C	Clyde	4

- After pressing [OK] in the dialogue box, the pivot table will be updated (the data will be added to the pivot table data source and the pivot table will be refreshed so as to include the new data in the calculations).

15.1.2 Insert rows into the data source

One way to add new rows of data to a pivot table **without** changing the data source is to **insert** the new rows of data into the existing data source rows. To do this:

- In the source data for the pivot table, insert one or more blank rows ABOVE any of the existing rows. (Note that if you instead insert rows below the data range, you will need to extend the data source range as explained in Section 15.1.1 above.)
 - Either, click on a cell in one of the existing data rows, then use the ribbon: Home tab > Cells group > Insert dropdown > Insert Sheet Rows,
 - Or, click on a cell in one of the existing data rows, then right-click > Insert... > Entire row,
 - Or, click on a row number of one of the existing data rows to select the entire row, then right-click > Insert.
- Enter the data into the newly inserted rows.
- Manually refresh the pivot table (see Section 14.1 above).

15.1.3 Use an “over-size” data source range

One strategy for setting up a pivot table when the data are not yet all entered is to simply include extra empty rows at the bottom of the data source for future data entry. This situation might occur when measurements or samples are taken at different times and you want to produce a pivot table for the results obtained so far. For example, if an experiment will produce 60 rows of data but so far only 20 rows of data have been entered, then when setting up the pivot table select a range of data cells that includes not only the available entered data rows but an additional 40 blank rows for data yet to be entered.

Note that as new data is entered, the pivot table **needs to be refreshed** (see Section 14.1 above) before the data appear in the table. Also note that having blank rows present in the data will cause “(blank)” to appear as a row or column label (see Section 8.1 on page 18 above).


15.2 Adding new columns of data

After creating a pivot table, as with adding rows (Section 15.1 above), it is possible to add further columns of data. There are a couple of ways that this can be done.

15.2.1 Adding new columns to the right of the data

After creating a pivot table, further columns of data may be added, e.g., as new data is collected. After adding any columns of data to the right of a pivot table data source, the data source needs to be updated before the extra columns can be used in the table. To update the data source:

- Click anywhere on the pivot table to ensure that the pivot table tools are visible in the ribbon.
- On the ribbon: Analyze tab > Data group > Change Data Source
- The “Change PivotTable Data Source” dialogue will appear.




	A	B	C	D	E	F	G	H
1	SampleID	Fruit	Temperature	Rep	Time_1	Time_2	Time_3	Time_4
33	32	Bananas	10	4	5	7	16	20
34	33	Kiwifruit	10	4	7	8	15	21
35	34	Kiwifruit	15	4	0	6	11	24
36	35	Apples	15	4	6	6	17	24
37	36	Apples	10	4	7	9	16	22

Columns to be added

- Extend the selection to include the extra columns (**Tip:** hold down the Shift key and press [Right arrow] to extend the selection to the right):

	A	B	C	D	E	F	G	H
1	SampleID	Fruit	Temperature	Rep	Time_1	Time_2	Time_3	Time_4
33	32	Bananas	10	4	5	7	16	20
34	33	Kiwifruit	10	4	7	8	15	21
35	34	Kiwifruit	15	4	0	6	11	24
36	35	Apples	15	4	6	6	17	24
37	36	Apples	10	4	7	9	16	22

- After pressing [OK] in the dialogue box, the pivot table will be updated (the data will be added to the pivot table data source and the pivot table will be automatically refreshed so as to include the new columns in the available pivot table fields).



15.2.2 Insert columns into the data source

One way to add new columns of data to a pivot table **without** changing the data source is to **insert** the new columns of data into the existing data source columns. This is particularly useful when you want to add more factors to use as either rows or columns of your pivot table. For example, you may have a column “Treatment” containing experiment treatments numbered 1-3, and want to add another column “TmtLabels” containing names for the treatments (e.g., “Low”, “Medium”, “High” etc.). To add one or more columns:

- In the source data for the pivot table, insert one or more blank columns **BETWEEN** any of the existing columns. (Note that if you instead insert columns to the left or to the right of the data range, you will need to extend the data source range as explained in Section 15.2.1 above.)
 - Either, click on a cell in one of the existing data columns, then use the ribbon: Home tab > Cells group > Insert dropdown > Insert Sheet Columns,
 - Or, click on a cell in one of the existing data columns, then right-click > Insert... > Entire column,
 - Or, click on a column letter of one of the existing data columns to select the entire column, then right-click > Insert.
- Enter the data into the newly inserted columns.
- Manually refresh the pivot table (see Section 14.1 above) so that the newly inserted columns become available as fields to use in the pivot table.

16 REARRANGING THE RAW DATA LAYOUT

16.1 Changing “wide” data to “long” (stacking data columns)

While it is best for statistical analysis to have the results for a single variable arranged all in one column, there are occasions (e.g., with repeated measurements made on the same thing) when it may be more convenient to enter the data into several columns side-by-side. Biometricians sometimes call the single column layout a “long” format and the side-by-side columns layout a “wide” format. You can use pivot tables to rearrange “wide” format data into a “long” format, a process often referred to as “stacking” the data.

NB: this method works only if the results are all numbers and there are no cells containing any text. If, for example, the data columns contained labels like “low”, “medium”, “high”, then this method will not work and you should [contact a biometrician](#) to discuss how to stack your data.

In this example, the results have been entered in a “wide” format with four adjacent columns (Time_1, Time_2, Time_3, Time_4) containing the results. To stack these data:

- Select all of the data and insert a pivot table into a new worksheet.

SampleID	Fruit	Temperature	Rep	Time_1	Time_2	Time_3	Time_4
1	Apples	15	1	5	11	15	24
2	Kiwifruit	5	1	2	8	10	20
3	Bananas	10	1	3	11	13	16
4	Apples	10	1	3	11	14	19
5	Dragonfruit	10	1	3	11	13	16

- Begin selecting the pivot table fields. For the pivot table rows, use all of the columns to the left of the results columns – these are usually factors that need to be repeated. Then for the “VALUES” fields select all of the results columns – these are the values that we wish to stack together into one column. The calculation can be any of Sum, Minimum, Maximum, or Average as these calculations will all return the original value.

PivotTable Fields

Choose fields to add to report: ⚙️

- ☒ SampleID
- ☒ Fruit
- ☒ Temperature
- ☒ Rep
- ☒ Time_1
- ☒ Time_2
- ☒ Time_3
- ☒ Time_4

Drag fields between areas below:

⏚ FILTERS

||| COLUMNS

Σ Values

≡ ROWS

SampleID

Fruit

Temperature

Rep

Σ VALUES

Sum of Time_1


Sum of Time_2

Sum of Time_3

Sum of Time_4

☐ Defer Layout Update UPDATE


- Change to the Classic pivot table layout by clicking anywhere on the pivot table, then on the ribbon: Analyze tab > PivotTable group > Options dropdown, select Options. In the PivotTable Options dialogue box, select the Display tab and select "Classic PivotTable layout (enables dragging of fields in the grid)". Press Enter, or click on [OK].



The pivot table layout will have changed.

				Values			
SampleID	Fruit	Temperature	Rep	Sum of Time_1	Sum of Time_2	Sum of Time_3	Sum of Time_4
1	Apples	15	1	5	11	15	24
		15 Total		5	11	15	24
	Apples Total			5	11	15	24
1 Total				5	11	15	24
2	Kiwifruit	5	1	2	8	10	20
		5 Total		2	8	10	20
	Kiwifruit Total			2	8	10	20
2 Total				2	8	10	20


- In the PivotTable Fields dialogue, Excel has created a Columns field named "Values". Drag-and-drop this field from Columns to Rows.



The values in the pivot table are now correct, but the appearance of pivot table needs tidying up.

SampleID	Fruit	Temperature	Rep	Values	Total
1	Apples	15	1	Sum of Time_1	5
				Sum of Time_2	11
				Sum of Time_3	15
				Sum of Time_4	24
		15		Sum of Time_1	5
		15		Sum of Time_2	11
		15		Sum of Time_3	15
		15		Sum of Time_4	24
	Apples			Sum of Time_1	5
	Apples			Sum of Time_2	11
	Apples			Sum of Time_3	15
	Apples			Sum of Time_4	24
1	Sum of Time_1				5
1	Sum of Time_2				11
1	Sum of Time_3				15
1	Sum of Time_4				24

- To change the appearance of the pivot table, remove the grand totals and sub totals. Ensure the pivot table tools are visible in the ribbon by clicking anywhere on the pivot table. On the ribbon: Design tab > Layout group > Subtotals dropdown, select "Do Not Show Subtotals".



- For instructions on removing the Grand Totals see Section 4.4.3 above.
- Fill in the empty label cells by clicking anywhere on the pivot table, then on the ribbon: Design tab > Layout group > Report Layout dropdown, select "Repeat All Item Labels".

SampleID	Fruit	Temperature	Rep	Values	Total
1	Apples	15	1	Sum of Time_1	5
1	Apples	15	1	Sum of Time_2	11
1	Apples	15	1	Sum of Time_3	15
1	Apples	15	1	Sum of Time_4	24
2	Kiwifruit	5	1	Sum of Time_1	2

- Change the name of the "Values" column to something more meaningful, in this case "Time". Unfortunately, the name of the "Total" column cannot be changed. The labels for the times can be improved by using Search-and-replace. In this example, "Sum of Time_" was replaced with nothing.

The resulting stacked data is now in a "long" format.

SampleID	Fruit	Temperature	Rep	Time	Total
1	Apples	15	1	1	5
1	Apples	15	1	2	11
1	Apples	15	1	3	15
1	Apples	15	1	4	24
2	Kiwifruit	5	1	1	2
2	Kiwifruit	5	1	2	8

17 WHEN PIVOT TABLES AREN'T ENOUGH

A spreadsheet is very good software for generalist data handling, and can do many things. However, Excel has limitations and when those are found it can be better to use specialist software instead. Statistical software, in particular, is designed to perform complicated analysis and data manipulation. The good news is that the ideal data arrangement for pivot tables in Excel is perfect for statistical packages. The statistical packages, Genstat, and Minitab can both read Excel files directly, or data can be copied and pasted from Excel into them. The software R can import data from Excel using commands (either from base R or from one of several add-on packages). Once, you have the data into the statistics package of your choice, then you can use the facilities of the statistics package to generate your required analysis and summary. If you need help with this, please talk to any of the [PFR biometricians](#).